

# APAX-5520CE/KW

# APAX-5620CE/KW

PAC with Marvel  
XScale® CPU

PAC with Marvel  
XScale® CPU and CAN



APAX-5520CE/KW

RoHS  
COMPLIANT  
2002/95/EC

CE FCC

## Specifications

### General

- **Certifications** CE, FCC class A
- **Dimensions (W x H x D)** 30 x 139 x 100 mm
- **Enclosure** ABS+PC
- **Weight** 210 g
- **Power Consumption** 4.5 W @ 24 V<sub>DC</sub> (typical)

### System Hardware

- **CPU** Intel XScale PXA270 520 MHz
- **Memory Flash** 32M bytes, SDRAM 64M bytes
- **Battery Backup Memory** 256 KB file system, 256 KB direct access
- **Real-time Clock** Yes
- **Watchdog Timer** Yes
- **VGA** DB15 connector
- **SB Ports** 1 x USB 1.1
- **Storage** 1 x Type II CompactFlash card slot

### Software

- **OS Support** Windows CE
- **Control Software** C/C++ and .NET library  
KW Multiprog (development tool)  
KW ProConOS (runtime kernel)

### I/O Expansion

- **Connected I/O Modules** 32 (max.)\*
- **Digital Signals** 2048 (max.)
- **Analog Signals** 512 (max.)

### Communication (Ethernet)

- **LAN Ports** 1 x RJ-45 Port, 10/100 Mbps
- **Offers Modbus/TCP Server and Client APIs**

### Communication (Serial)

- **Medium** 1 x Isolated RS-485 (2-wire, isolated)
- **Offers Modbus/RTU Master and Slave APIs**

### Environment

- **Operating Temperature** -10 ~ 55 °C (when mounted vertically)
- **Storage Temperature** -40 ~ 70° C
- **Relative Humidity** 5 ~ 95% (non-condensing)

## Ordering Information

- **APAX-5520CE-AE** PAC with Marvel XScale CPU, WinCE
- **APAX-5520KW-AE** PAC with Marvel XScale CPU, KW

### Accessories

- **APAX-5002-AE** 2-slot Backplane Module
- **APAX-5343E-AE** Power Supply for APAX Expansion Module

\*APAX DI/O modules can use ID number 0 ~ 31, while AI/O modules and counter modules can only use ID numbers 0 ~ 15



APAX-5620CE/KW

RoHS  
COMPLIANT  
2002/95/EC

CE FCC

## Specifications

### General

- **Certifications** CE, FCC class A
- **Dimensions (W x H x D)** 60 x 139 x 100 mm
- **Enclosure** ABS+PC
- **Weight** 310 g
- **Power Consumption** 11 W @ 24 V<sub>DC</sub> (typical)

### System Hardware

- **CPU** Intel XScale PXA270 520 MHz
- **Memory Flash** 32M bytes, SDRAM 64M bytes
- **Battery Backup Memory** 256 KB file system, 256 KB direct access
- **Real-time Clock** Yes
- **Watchdog Timer** Yes
- **VGA** DB15 connector
- **USB Ports** 1 x USB 1.1
- **Storage** 1 x Type II CompactFlash card slot

### Software

- **OS Support** Windows CE
- **Control Software** C/C++ and .NET library  
KW Multiprog (development tool), KW ProConOS (runtime kernel)

### I/O Expansion

- **Connected I/O Modules** 32 (max.)\*
- **Digital Signals** 2048 (max.)
- **Analog Signals** 512 (max.)

### Communication (Ethernet)

- **LAN** 2 x RJ-45 Port, 10/100 Mbps
- **Offers Modbus/TCP Server and Client APIs**

### Communication (Serial)

- **Medium** 2 x Isolated RS-485 (2-wire, isolated)
- **Offers Modbus/RTU Master and Slave APIs**

### Communication (CAN)

- **Medium** Isolated CAN x 2
- **Protocol** CANopen
- **Speed** maximum 1 Mbit/s

### Environment

- **Operating Temperature** -10 ~ 55 °C (when mounted vertically)
- **Storage Temperature** -40 ~ 70° C
- **Relative Humidity** 5 ~ 95% (non-condensing)

## Ordering Information

- **APAX-5620CE-AE** PAC with Marvel XScale CPU, CAN, WinCE
- **APAX-5620KW-AE** PAC with Marvel XScale CPU, CAN, KW

### Accessories

- **APAX-5002-AE** 2-slot Backplane Module
- **APAX-5343E-AE** Power Supply for APAX Expansion Module