

FPM-7211W

21.5" Industrial Monitor with Projected Capacitive Touchscreen, Direct-VGA and DVI Ports



Features

- 21.5" Full HD TFT LED LCD wide screen display
- Truly-flat touch screen with IP65 compliance
- Slim type design for Panel mount / Wall mount easy installation
- Supports industrial 24V_{DC} power input
- Supports panel, wall, desktop and VESA arm mounting

Introduction

With its brand new design, the FPM-7211W provides a new wide screen display size with industrial grade design concept. With a truly-flat touch screen, the front bezel meets IP65 testing criteria. The light weight FPM wide screen monitor with slim enclosure is ideally suited to being either panel or wall mounted.

Specifications

General

- **OSD Controls** OSD control in rear cover
- **Certification** BSMI, CCC, CE, FCC Class A, UL
- **Dimensions (W x H x D)** 561x356x45.7mm (22.1"x14"x1.8")
- **Enclosure** Front panel: Die-cast Magnesium alloy
Rear cover: SECC
- **Mounting** Panel, wall, desktop, VESA arm
- **Power Input** Phoenix Jack: 24 V_{DC} input
DC Jack: external 57 W power adapter, with 100 ~ 240 V_{AC} input and 12 V_{DC} @ 4.75 A output

Note: AC power adapter is included.

- **Power Consumption** 35 W + 20%
- **Video Port** VGA & DVI-D port
- **Weight (Net)** 8kg (17.6lbs)

LCD Display

- **Display Type** Full HD TFT LED LCD
- **Display Size** 21.5"
- **Max. Resolution** 1920 x 1080
- **Max. Color** 16.7 M
- **Viewing Angle (H/V°)** 178/178
- **Luminance (cd/m²)** 300
- **Backlight Life (hrs)** 50,000
- **Contrast Ratio** 5000:1

Touchscreen


- **Type** Projected Capacitive touch
- **Interface** RS-232 and USB
- **Light Transmission** Above 75%
- **OS Support** Microsoft® WES7P/XP/WES2009/WinCE 6.0/ Linux

Environment

- **Operation Temperature** 0 ~ 50°C (32 ~ 122°F)
- **Storage Temperature** -20 ~ 60°C (-4 ~ 140°F)
- **Humidity (Storage)** 10 ~ 90% non-condensing
- **Waterproof** Front panel is IP65 compliant
- **Vibration** 5 ~ 500 Hz, 1 Grms (Operating, Random)

Dimensions

Unit: mm



Panel Cut-out Dimensions: 550.5mm x 345.2mm

Ordering Information

- **FPM-7211W-P3AE** 21.5" Full HD Ind Monitor w/PCT TS (RS-232, USB)

Accessories

- **PWR-246E** Ind. DC to DC w/24-48 V_{DC} 1.4-2.9A In 12 V_{DC} 5A Out
- **1702002600** Power Cable US Plug 1.8 M
- **1702002605** Power Cable EU Plug 1.8 M
- **1702031801** Power Cable UK Plug 1.8 M
- **1702031836** Power Cable China/Australia Plug 1.8 M

Rear View



- TS Interface - RS232 Port
- TS Interface - USB Port
- 24V_{DC} Power Input with Phoenix Jack
- 12V_{DC} Power Input with DC Jack
- DVI Port
- VGA Port