

TPC-GS1051HT V4

Pictures:





Features:

1. 10.1'' Multi-touch capacitive touch screen
2. Chipset: Intel® Celeron N2930 Quad-core CPU, up to 2.16Ghz
3. Provide WiFi and BT(Standard)
4. Onboard 4GB DDR3 RAM(Standard)
5. Battery: 7.4V 5300mAh, work for 8 hours
6. Optional: GPS/NFC/RFID/2D optional
7. Fanless & wireless High-strength and elegant Al-alloy panel

Specification:

Display	Screen	10.1" TFT LED
	Resolution	1280*800
	brightness	400 cd/m2
	Contrast	1000: 1
	Touchscreen	Multi-touch Capacitive touch With Capacitance pen
Performance	Chipset	Intel® N2930 1.83GHz Quad-core; up to 2.16 Ghz
	RAM	On board 4GB; max 8GB
	Hardware Monitor	Monitors voltage, TEMP
	Watchdog Timer	0-255 sec by software
	Storage	SSD: 64GB
Power	consumption	11w(standby), 18w(rated power)
	Power Supply	12V DC
	Battery	Li-ion Battery: 5300 mAh 8Hours Duration

O/S	O/S	Windows 7/ 8 /10/ Linux
Camera	Camera	Front 200W / Back 500W
I/O Port	USB	1*USB 3.0 / 1*USB 2.0
	Serial	DB 9,1-2*RS232/422/485
	Ethernet	1* GbE LAN RJ45
	Audio	Speaker/MIC
	Display	1*mini HDMI
	Extension	1*Mini PCIe:(3G /4G)
Optional	GPS	Beidou+GPS 2-in-1
	2D Scan	1D/2D(code39/UPC/EAN/code93)
	RFID	ISO14443TYPEA/B,ISO15693 MIFARE /DESFIRE/ICODE2/AT020
Environmental	Anti-vibration	5-19Hz/1.0mm amplitude;19-200Hz/1.0g, acceleration
	Anti-shock	10g acceleration, 11ms duration
	IP Level	IP65
	Reliability	MTBF≥50000h; MTTR≤0.5h
	Operating Temperature	-20℃--60℃ with air flow
	Storage Temperature	-30℃ --70℃
	Operating Humidity	95% @40℃, non-condensing
Mechanical	Dimensions	274*194*26.5 Without Cover Angle
	Material	Fanless High-strength and elegant Al-alloy panel
	Weight	1.3kg/1.5kg(NET/Gross)